## Technical specification/ Data sheet

## Alarm cable 4 cores with screen: SEC4S-HQ

| Product Specification                 |                          |                  |
|---------------------------------------|--------------------------|------------------|
| ltem:                                 | SEC4S-HQ                 |                  |
| Materials                             |                          |                  |
| 1. Inner Conductor                    | Nominal O.D.:            | 4 cores 7x0.16mm |
|                                       | Material:                | Bare Copper      |
| 2. Insulation                         | Nominal O.D.:            | 1.0mm            |
|                                       | Material                 | PVC              |
| 3. Jacket                             | Color                    | White            |
|                                       | Nominal O.D.:            | 3.4±0.1mm        |
|                                       | Material                 | PVC (CPR Eca)    |
| 4. Foil Shield                        | Coverage                 | 100%             |
|                                       | Material                 | AL/Foil          |
| Core Colors                           | Red, Blue, Yellow, Black |                  |
| ELECTRICAL CHARACTERISTICS (@20°C)    |                          |                  |
| Max Conductor Resistance<br>(ohms/km) | 230                      |                  |
| Core Spark Test Voltage (KV)          | 2.5                      |                  |
| Rated temperature                     | <b>70</b> ℃              |                  |



SIA "YT Group", Lizuma iela 1, Rīga, LV-1006, tālr.: 67801 301, fakss: 67801 300, ytgroup@ytgroup.lv