

Technical specification/ Data sheet

Loudspeaker cable: FB-1.00 CA

Specification													
Product description Unshielded double line with stranded core made of CCA Intended use Interconnection of loudspeaker systems For the transmission of low frequency signals Construction 2 cores _____ insulation wires	FB-1.00 CA 												
Cable construction <table><tr><td>Inner Conductor</td><td>Copper-clad aluminium</td></tr><tr><td>Diameter of inner conductor</td><td>0.12mm x 91</td></tr><tr><td>Conductor cross section</td><td>1.00 mm²</td></tr><tr><td>Cable jacket</td><td>PVC</td></tr><tr><td>Diameter</td><td>2.8x5.6mm</td></tr><tr><td>Color</td><td>Transparent</td></tr></table>	Inner Conductor	Copper-clad aluminium	Diameter of inner conductor	0.12mm x 91	Conductor cross section	1.00 mm ²	Cable jacket	PVC	Diameter	2.8x5.6mm	Color	Transparent	
Inner Conductor	Copper-clad aluminium												
Diameter of inner conductor	0.12mm x 91												
Conductor cross section	1.00 mm ²												
Cable jacket	PVC												
Diameter	2.8x5.6mm												
Color	Transparent												
Marking FB-1.00 FlexBox LOUDSPEAKER HI-FI CABLE 1.00 mm ² ISO9002 Euroclass Eca													