

## O5A 06W - Omnidirectional 5G Antenna

Art. Number 109602

<u>triax.com</u>



360° antenna for 4G/5G signal reception.

## Future-proof connectivity, wherever you are

Work, rest or play online reliably and quickly, wherever you're staying - TRIAX 5G antennas boost mobile broadband reception in places fibre doesn't reach.

Simply connect to your choice of mobile broadband router to receive the maximum attainable mobile network speed at each location.

The antennas are ready for the advancing 5G roll-out across Scandinavia, bringing speeds up to 100x faster than 4G. They are fully compatible with all mobile signals: use the best possible 4G LTE speeds now, with no need for future upgrades when 5G arrives.

For the ultimate in speed and reliability, our antennas are MIMO compatible.

The antenna is delivered with 2m white twin cable with connectors, which are ready for mounting directly on the 2 antenna inputs on the router.

| Technical Specifications |   |  |
|--------------------------|---|--|
| ORDER INFORMATION        |   |  |
| EAN Number               | 5702661096020                             |  |
| CHARACTERISTICS          |   |  |
| Antenna type             | omnidirectional                           |  |
| Antenna use              | indoor & outdoor                          |  |
| MIMO                     | Yes                                       |  |
| Polarization             | Antenna 2 - vertical                      |  |
| FREQUENCY RANGE          |   |  |
| Frequency range   MHz    | 698-960/1710-2700/3300-3600/4800-5000 MHz |  |
| Services                 | GMS/Wi-Fi/3G/4G/LTE/5G - (5G low band)    |  |



| Technical Specifications              |   |  |
|---------------------------------------|---|--|
| GAIN                                  |   |  |
| Gain  dBi                             | 46 dBi  |  |
| VSWR                                  | 3   |  |
| ELECTRICAL                            |   |  |
| Front to back ratio - horizontal   dB | > 21 dB                                       |  |
| Impedance   Ω                         | 50 Ω  |  |
| OPERATIONAL                           |   |  |
| IP rating                             | 65  |  |
| Lightning protection                  | DC ground on the antenna                      |  |
| Temperature - operating   °C          | -40 +60 °C                                    |  |
| CONNECTORS                            |   |  |
| Connector Type                        | 2 x SMA-male                                  |  |
| Output cable lenght   m               | 2x2 m   |  |
| Output cable type                     | PVC white UV protected low loss coaxial cable |  |
| MECHANICAL                            |   |  |
| Beamwidth horizontal   °              | 360 °   |  |
| Beamwidth vertical   °                | 120 °   |  |
| Bracketry                             | with wingnuts                                 |  |
| Colour                                | RAL 1013 - White                              |  |
| Product Depth   mm                    | 70 mm   |  |
| Diameter of installation pole   mm    | 30-53 mm                                      |  |
| Packaging Depth   m                   | 0.089 m                                       |  |
| Packaging Height   m                  | 0.223 m                                       |  |
| Total Weight   kg                     | 0.890 kg                                      |  |
| Packaging Width   m                   | 0.221 m                                       |  |
| Product Height   mm                   | 200 mm  |  |
| Product Length   mm                   | 215 mm  |  |
| Main material                         | Plastic housing ABS                           |  |
| Net Weight   kg                       | 0.750 kg                                      |  |
| Packing QTY                           | 1   |  |
| Tara Weight   kg                      | 0.140 kg                                      |  |
| Packaging Volume   m3                 | 0.004 m3                                      |  |

