

TDS 80A RAL 7016, bulk pack

Art. Number 120510



TRIAX TD Dishes The difference is clear

Manufactured and tested to the highest standards of precision and quality, TRIAX's easy-to-install dishes offer outstanding performance, durability and reliability.

TDS: Steel TDA: Aluminium

- Unrivalled build quality, whether Steel or Aluminium
 - Hot-dip galvanized steel OR long lasting Aluminium - for extra corrosion protection
 - TRIAX's unique cable protection system
 - Every part, every accessory is weatherproofed
 - 2 years corrosion warranty
 - 5 years functionality warranty
- Outstanding performance
 - High gain for an exceptional signal
- Quick and easy installation
 - One-click mounting system
 - Self-locking screw & nuts
- Logistic friendly
 - Single or Bulk packaging, according to customer needs

TRIAX is your reliable partner, with comprehensive service and support.

[Click here](#) to see our guide on how to install TRIAX satellite dishes.

Technical Specifications

ORDER INFORMATION

EAN Number 5702661205101



TRIAx

connecting the future

Technical Specifications

CHARACTERISTICS

Elevation range °	0...90 °
F/D ratio	0,62
G/T LNB 0.7 dB/K	17.3 dB/K
Offset angle °	25.6 °
X-polarisation dB	≤ -27 dB

FREQUENCY RANGE

Frequency range GHz	10.7...12.75 GHz
-----------------------	------------------

GAIN

Gain @ 11.7 GHz dBi	37,5 dBi
-----------------------	----------

MECHANICAL

Arm Colour	Raw
Beamwidth °	2.6 °
Colour	RAL 7016 - Anthracite grey
Packaging Depth m	0.790 m
Packaging Height m	0.011 m
Total Weight kg	4.515 kg
Packaging Width m	0.710 m
Height (cm) cm	79 cm
LNB holder	40
Main material	Galvanized steel (hot-dip)
Mast bracket diameter mm	32...60 mm
Net Weight kg	4.420 kg
Packing QTY	200
Reflector type	Offset
Tara Weight kg	0.095 kg
Packaging Volume m3	0.006 m3
Width (cm) cm	71 cm